



SIGN FLAT ON WALL



FLAG MOUNT



CEILING MOUNT



CHAIN MOUNT

Ecoglo “Accessible” S20 Signs are designed to be used in and about buildings to identify accessible routes and facilities provided specifically for people with disabilities. The sign will be clearly visible and readily understandable under all conditions of foreseeable use, including emergency conditions.

SIGN DEFINITION

Access and facilities for people with disabilities.

PERFORMANCE

Ecoglo “Accessible” S20 Signs being photoluminescent will continue to be visible indoors after failure of the main lighting, and outdoors after dark.

UV Resistance - Loss of luminance after 1000 hrs ASTM G-155 Cycle 1 exposure: <10%: Pass

Salt Spray Resistance - ASTM B117: Pass

Washability - ASTM D4828: Pass

Rate of Burning - ASTM D635: Pass

Surface Flammability - ASTM E162: Pass

Toxicity - Bombardier Toxic Gas Generation Test SMP800-C: Pass

Radioactivity - ASTM D3648: Pass

COMPOSITION

The high visibility flat panel is manufactured from 5005 0.9mm aluminium sheet. Custom made photoluminescent pigments are embedded in thermoset polyester carriers to integrally bond the active ingredients onto the aluminium sheet following curing at high temperature.



INSTALLATION

Standard signs and outdoor signs are supplied with fixers for mounting flat on a wall. Brackets for ceiling or flag mounting are also available.

ORDERING

The sign is available in the following size

PRODUCT CODE	PRODUCT	SIGN SIZE
Standard Sign		
S20-AC1616	Accessible	162mm x 162mm
Outdoor Coated Sign		
S20-AC1616C	Accessible	162mm x 162mm
Mounting Brackets		
BR1-162	Ceiling Mount Bracket for S20-AC1616 sign	
BR1-162	Flag Mount Bracket for S20-AR1616 sign	

Chain suspension is also available.

Contact

Ecoglo International Limited

Email: info@ecoglo.com Web: www.ecoglo.com